

TOWER CRANE N7527-20



Hunan Kamuja Machinery & Equipment Co, Ltd







FACTORY INTRODUCTION





Founded in 1958, the manufacture is an industry-leading enterprise integrating the R&D, manufacturing, installation, transformation and maintenance of construction hoisting machinery, and is also one of the first four manufacturers who obtained the manutacture license of construction machinery in China.

Two production bases in Bali and Wuming of Nanning, covering an area of 360,000 square meters and equipped with more than 1,200 sets of advanced processing equipment, with an annual output of over RMB 3 billion.

PRODUCT INTRODUCTION

★ Internal climbing type tower crane: The tower crane is Installed inside a building, and cumbs upward with the help o the building structure, without any independent foundation. additional attachment devices or standard sections. Such a tower crane features a low cost, a wider construction coverage area and higher work efficiency. Furthermore, such a tower crane can transformed into an attached tower crane at a low cost.

★ Inner cage type tower crane: The Jacking center of gravity rests on the center of the tower body, making the installation, removal, and lifting of the tower crane more stable, and safer. The standard sections of the tower body are of a sheet structure which occupies less space during transportation and storage, thus lowering the cost or transportation and storage. It can be accessed in any angle within the range of 360°.



★ Outer cage type tower crane: The standard sections of the tower body can be installed and removed as a whole, making such a tower crane easy for connection, safe and relablein operation. and quick in lifting up and down.

HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.

Room 818, 4th Floor, Chang Tong Logistic Center, No.18 Qingzhuhu Road, Changsha, Hunan, China Tel: +86 0731 88677248 E-mail: juana.yan@kamuja.cn













FEATURES





System integration, intelligent lifting:

Highly-integrated intelligent electrical monitoring, smooth lifting. Varying load and speed, accurate positioning, full coverage of real-time monitoring. risk identification without blind corner.





Triple protection. safe and reliable:

Anti-slip hook, anti-overload, anti-punching, anti-tower-falling, anti-rope-breaking, anti-collision, anti hanging. anti-swing and anti-twist safety functions. Providing triple protections by means or mechanical. electronic and intelligent technologies.





Ouick assembly design, convenient assembly and disassembly:

Quick assemply platform, combied tie rod, telescopic wall attachment. error-proof aviation plug, quick assembly and disassembly, flexible and efficent.











High Efficiency, worry free service:

Open type tower body, easy maintenance, long service life; sheet-like standard mast, stacked storage, low transport cost; sate operation, worry Tree service, fine management, economic operation the through the whole lite cycle under the support from "Construction Machinery Smart Housekeeper"

First-class configuration, excellent performance:

Three major transmission mechanisms, hydraulic jacking device, intelligent electrical system, intelligent monitoring system and other components all suppled by First-class manufacturers: high rigidity, good stability and high wind resistance of the structure, ensuring more rellable operation of the machine.



CUSTOMER REFERENCE



















Room 818, 4th Floor, Chang Tong Logistic Center, No.18 Qingzhuhu Road, Changsha, Hunan, China Tel: +86 0731 88677248 E-mail: juana.yan@kamuja.cn












N7527–20 Flat–top Tower Cranes

Drawing of tower crane structure 21.6m 76.56m 75m 2.7t 11.8m 3.0m 6.8m 70m 3.3t 3.0m 6.8m 11.8m 65m 3.9t 10 11.8m 3.0m 6.8m 60m 4.5t 11.8m 3.0m 6.8m 55m 5.2t 50m 6.3t 11.8m 6.8m (2)=10m 3 = 10m 11.8m 6.8m $\overline{4}$ = 5m \bigcirc = 5m 6 = 5m 6.8m 7 = 5m 8 = 5m 9 = 5m 40m 8.3t 6.8m 35m 9.1t 0 = 5 m11 = 5m(12) = 5 m30m 11.0t

TOWER




Sectional dimensions of tower section(m×m×m)	Reinforced section	Standard section	ndard section FSH(m)				
2.0*2.0*3.0(outer cage)	8	9	62	350			

HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.

Room 818, 4th Floor, Chang Tong Logistic Center, No.18 Qingzhuhu Road, Changsha, Hunan, China Tel: +86 0731 88677248 E-mail: juana.yan@kamuja.cn











Load Diagrams

\triangle	R (m)	12. 6	14. 0	16. 0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0	52. 0	54. 0	56. 0	58. 0	60.0	62. 0	64. 0	66. 0	68. 0	70. 0	72. 0	74. 0	75. 0
75. 0	00				10. 00				9. 57	8. 82	8. 17	7. 60	7. 10	6. 65	6. 25	5. 89	5. 57	5. 27	5. 00	4. 75	4. 53	4. 32	4. 12	3. 94	3. 77	3. 62	3. 47	3. 33	3. 20	3. 08	2. 96	2. 86	2. 75	2. 70
70.0	00	20. 00	17. 88	15. 44	13. 55	12. 03	10. 79	9. 75	8. 87	8. 12	7. 47	6. 90	6. 40	5. 95	5. 55	5. 19	4. 87	4. 57	4. 30	4. 05	3. 83	3. 62	3. 42	3. 24	3. 07	2. 92	2. 77	2. 63	2. 50	2. 38	2. 26	2. 16	2. 05	2. 00
	R (m)	13.7	14. 0	16. 0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0	52. 0	54. 0	56. 0	58. 0	60.0	62. 0	64. 0	66. 0	68. 0	70. 0			
70.0							10.00			9. 67	8.96	8. 45	7.80	7. 31	6.88	6. 49	6. 13	5. 88	5. 52	5. 25	5. 00	4. 77	4. 56	4. 36	4. 18	4. 01	3.85	3. 70	3. 56	3.43	3. 30			
70.0	80	20.00	19.58	16. 93	14. 86	13. 22	11.87	10.74	9.79	8. 97	8. 26	7. 65	7. 10	6. 61	6. 18	5. 79	5.43	5. 11	4. 82	4. 55	4. 30	4. 07	3.86	3. 66	3. 48	3. 31	3. 15	3. 00	2. 86	2.73	2. 60			
	R (m)	14.5	16.0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0	52. 0	54. 0	56. 0	58. 0	60.0	62. 0	64. 0	65.0				•		
							10.00			9.56	8. 90	8. 32	7. 88	7. 35	6. 93	6.56	6. 22	5. 91	5. 62	5. 36	5. 12	4. 89	4. 68	4. 49	4. 31	4.14	3.98	3. 90						
65.0		20. 00	18. 00	15. 85	14. 12	12. 67	11.48	10. 47	9. 61	8.86	8. 20	7.62	7. 11	6. 65	6. 23	5.86	5.52	5. 21	4. 92	4. 66	4. 42	4. 19	3. 98	3. 79	3. 61	3. 44	3. 28	3. 20						
\wedge	R (m)	15. 0	16. 0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0	52. 0	54. 0	56. 0	58. 0	60.0				_					
	6				10.	00				9.95	9. 27	8. 67	8. 13	7. 66	7. 23	6.84	6. 48	6. 16	5. 87	5. 59	5. 34	5. 11	4. 89	4. 69	4. 50									
60.0	100 100	20.00	18. 77	16. 51	14. 69	13. 21	11.97	10. 92	10.03	9. 25	8. 57	7.97	7. 43	6. 96	6. 53	6.14	5. 78	5. 46	5. 17	4. 89	4. 64	4. 41	4. 19	3. 99	3.80									
\wedge	R (m)	15. 6	16. 0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0	52. 0	54. 0	55. 0			ı								
	<u> </u>					10.00					9. 62	9.00	8. 45	7. 95	7.51	7. 11	6. 74	6. 41	6. 10	5. 82	5. 56	5. 32	5. 20											
55. 0	201	20. 00	19. 48	17. 14	15. 26	13. 72	12. 44	11.36	10.43	9. 63	8. 92	8.30	7. 75	7. 25	6. 81	6. 41	6. 04	5. 71	5. 40	5. 12	4.86	4. 62	4. 50											
/\/\	R (m)	16.7	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	46. 0	48. 0	50. 0					1										
	<u> </u>					10.00					9. 71	9.12	8. 59	8. 12	7. 68	7. 29	6.93	6. 61	6. 30															
50. 0		20.00	18. 48	16. 47	14. 82	13. 45	12. 29	11.30	10. 43	9. 68	9. 01	8. 42	7. 89	7. 42	6. 98	6. 59	6. 23	5. 91	5. 60															
	R (m)	16.7	18. 0	20.0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	36. 0	38. 0	40. 0	42. 0	44. 0	45. 0			1														
	6					10.00					9. 71	9.12	8. 59	8. 12	7. 68	7. 29	7. 10																	
45. 0	<u> </u>	20. 00	18. 48	16. 47	14. 82	13. 45	12.99	11.30	10. 43	9. 68	9. 01	8. 42	7.89	7. 42	6. 98	6. 59	6. 40																	
/\/\	R (m)	17. 0	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30.0	32. 0	34. 0	36. 0	38. 0	40. 0				l																
	bd					10.00					9.94	9.33	8. 66	8. 30																				
40. 0	201	20. 00	18. 9	16. 85	15. 17	13. 77	12.58	11.57	10. 68	9.92	9. 24	8.63	8. 09	7. 60																				
/\/\	R (m)	17.3	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0	32. 0	34. 0	35. 0																						
	bd					10.0	00					9.80																						
35. 0		20. 00	19. 25	17. 16	15. 45	14. 03	12.82	11. 79	10.90	10.11	9.42	9.10																						
/\/\	R (m)	17.5	18. 0	20. 0	22. 0	24. 0	26. 0	28. 0	30. 0				I																					
	bd				10.	00				l																								
30. 0	9	20. 00	19.43	17. 33	15. 60	14. 17	12. 95	11.91	11.00																									
	$ \Omega \Omega $	20.00	. 7. 43		.0.00	/ //	12.75	/ 1	1]																								

HUNAN KAMUJA MACHINERY & EQUIPMENT CO.,LTD.

Room 818, 4th Floor, Chang Tong Logistic Center, No.18 Qingzhuhu Road, Changsha, Hunan, China Tel: +86 0731 88677248 E-mail: <u>juana.yan@kamuja.cn</u>










Main Technical Parameters

Hoisting	Rated hoisting mon	nent	3150kN.m								
performance	Maximum hoisting cap	20 t									
Mechanism	2Fall		41	Motor							
performance	t	m/min	t	m/min	Motor						
Lifting	5	0~90	10	0~45	001/						
Lifting	10	0~45	20	0~22.5	90Kw						
Trolleying	0~65 m/min										
Slewing	0~0.66 r/min										

X The technical information may vary by the update policy, the changes will be without prior notice.







Hunan Kamuja Machinery & Equipment Co.,Ltd

Address: Qingzhu Hu Road N.18, Chang Tong Logistic Center Floor 4 Room 818, Jinxia Economic Development Zone, Changsha City, Hunan Province, P.R of China.

333 SE 2nd Avenue Suit 2000 Miami FL 33131. USA

Tel: +86 731 8867 7248 e-mail: info@kamuja.cn

Web site: www.kamuja.cn



